

ZH520

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -5500 lumens and IP6X certified
- Compact for easy installation 1.3x zoom, 360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency

The ZH520 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹



An added benefit, the ZH520 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

EAN: 5055387667754, Colour: White UPC: 796435 44 693 2, Colour: White

Display/image DLP™

Display technology

1080p Full HD (1920x1080) Resolution

Brightness 5.500 lumens Contrast ratio 3,000,000:1 Native aspect ratio 4:3,16:9,16:10 Aspect ratio - compatible

309 Keystone correction horizontal

30° Keystone correction - vertical Displayable colours (millions) 1073.4 Uniformity 75%

Lamp info Light source type Laser LASER life 30,000 hours

Optical Throw ratio 1.13:1 ~ 1.47:1 Projection distance (m) 1m - 8m Zoom 1.3 Zoom type Manual 16.90 ~ 21.61 Focal length (mm) Native offset 116%

Connectivity

3D compatibility

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General Noise level (typical) 29dB Noise level (max) 31dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r

Security Security bar, Kensington Lock, Password protected interface

IP6X IP rating

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese 24/7 operation Yes

360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

Card style Remote control Speaker count Watts per speaker 15W In the box AC power cord Remote control

1x CR2025 battery Basic user manual

UHDCast Pro Optional wireless models

Power

External power supply, 100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 128W 205W Power consumption (max)

Weight and dimensions Dimensions (W x D x H) mm

274 x 216 x 108 Gross weight 4.6 kg 3.4 kg Net weight



