







EP1691i

DLP® Projector

Ultra light, ultra bright widescreen projector

-  Light and ultra portable – only 1.4kg
-  Native WXGA, 2500:1 contrast ratio – ideal with Widescreen & HD sources for sharp detailed images
-  Conference room brightness – 3000 ANSI Lumens
-  Ideal presentation remote with mouse control & laser pointer
-  Rapid power on and shutdown – saving you time & money
-  DLP® filter-free design – Virtually no maintenance



HD
ready



HD
ready

Incredible Brightness from a Portable Widescreen Projector

Light, bright and beautifully designed

Widescreen and HD Ready; the EP1691i brings together amazing brightness, portability and cutting-edge design in one travel-friendly DLP® projector.

Weighting only 1.4kg with a staggering 3000 ANSI Lumens, perfect for large rooms and light enough to be taken on the road. Ideally partnered with a widescreen notebook and HD sources, to deliver bright vivid presentations and videos.

Small doesn't mean that you miss out on specification though, this projector still comes with an HDMI input for digital clarity, filter-free, low maintenance design and our unique 5 year Optoma Colour and Imager guarantees.

STAGGERING BRIGHTNESS

Project in brightly lit locations with the powerful 3000 ANSI Lumens to define the smallest screen details clearly. Your audience will experience the EP1691i remarkable picture in almost any lighting situation.

TRUE WXGA RESOLUTION

The EP1691i is the perfect companion for widescreen laptops. Your presentations will appear as sharp and detailed as they do on your widescreen laptop in WXGA (1280 x 800). WXGA resolution gives 30% more pixels than XGA.



TRUE HDMI

Project crystal clear images using the latest HDMI v1.3 input. Hassle-free projection from a widescreen computer/HD source with a single HDMI cable – no need for separate audio cables.



Travelling with a lightweight, EP1691i portable DLP® projector is convenient and hassle-free.

CARRY BAG

A luxury carry case is provided for you to be able to take the EP1691i anywhere, anytime.



SAVING TIME & ENERGY

It takes less than 10 seconds for the projector to power up and shutdown, so the EP1691i not only saves time but energy too.

The timer control functions turn the projector off when it is not in use helping to save energy and extend the lamp life of your projector.

CUSTOMISED START UP SCREEN

First impressions are important so set the company logo as your start up screen to make that lasting impression.

FEATURES

- 5 preset picture modes
- Quick keystone correction
- Easy to use on the table or ceiling mounted
- Fully featured remote with mouse control & laser pointer

AMAZING COLOUR AND IMAGE PERFORMANCE



The EP1691i incorporates BrilliantColor™ technology for vibrant like-like colours that brings to life any image displayed.

Stunning 2500:1 contrast ratio for pin sharp graphics and crystal clear text.

COLOUR PERFORMANCE

Optoma guarantees colour quality will remain as new for 5 years*



We are so confident that the EP1691i colours will not fade that we guarantee the colours will remain vibrant and vivid, even after many years of use.

IMAGE PERFORMANCE

Optoma guarantees image quality will remain as new for 5 years***




Optoma projectors are designed with DLP® technology, preventing degradation over time and consistent pixel performance. The Imager Guarantee ensures a precise picture performance for a minimum of 5 years.

Image and colour enhancement technologies

**WITH
2500:1 contrast ratio**



**WITHOUT
400:1 contrast ratio**



BrilliantColor™ Technology

Advanced colour processing for bright, vivid, lifelike colour.

*Simulated Images

Maintenance FREE = Lower Total Cost of Ownership (TCO)

DLP® technology ensures lower cost of ownership, longer life and improved reliability compared to other technologies.

The filter-free projector design means no more regular filter cleaning or replacements, saving you time and money.



Present exactly what's on your PC screen without adjustments



EP1691i

Specifications

EP1691i	
Native Resolution	WXGA 1280 x 800
Compressed Resolution	up to UXGA (1600 x 1200)
Brightness	3000 ANSI Lumens
Contrast	2500:1
Noise Level (STD mode)	33dB
Lamp Life	3000/2000 (STD/BRIGHT mode)
Display Technology	Single 0.65" WXGA type A DMD chip
Weight / Dimensions (W x D x H)	1.4 kg / 220 x 178 x 71
Remote Control	Full Function Remote Mouse with Laser and Direct Source selecting
INPUTS:	HDMI (HDCP) - Audio Supported 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite 3.5mm Stereo Jack USB (remote mouse)
Audio	1 x 1W Speaker
Aspect Ratio	16:10 Native, 16:9, 4:3 Compatible
Keystone Correction	± 30° Vertical
On Screen Display	17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish & Arabic
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i
Uniformity	80%
Displayable Colours	134.2 Million
Projection Lens	F=2.55 ~ 2.72, f=21.3 ~ 24.5mm, 1.15x Manual Focus
Throw Ratio	1.5 ~ 1.8:1 (Projection Distance:Image Width)
Projection Distance	1.2 - 12m
Image Size	0.79 - 9.43m (30.95" - 371.42") Diagonal 16:10
Horizontal / Vertical Scan Rate	15 - 91.4kHz / 43 - 87Hz
Lamp Type	220W Lamp
Power Supply	100-240V, 50-60Hz with PFC Power Supply
Power Consumption	280W BRIGHT mode < 5W Standby mode 230W STD mode < 5W Standby mode
Operating Conditions	Operating: 5 - 40°C, 80% Humidity (Max), 3000m Altitude (Max)
Security	One Kensington Lock Port, Password Protection
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Soft Carry Bag, Quick Start Guide, CD User Manual, Warranty, WEEE Card
RoHS	Compliant
Lamp Warranty	6 months or 1000 hours - whichever comes sooner
Warranty	Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details

Easy to use remote control



EP1691i Remote Control

- 1 Laser
- 2 Remote Mouse
- 3 Vertical Keystone Correction
- 4 Volume Control
- 5 Brightness Adjustment
- 6 AV Mute
- 7 Direct Input Source Selection

EP1691i Connections

- 8 USB (remote mouse)
- 9 Audio In
- 10 S-Video
- 11 Composite
- 12 VGA In – Component & SCART via adaptor
- 13 HDMI (audio supported)
- 14 Kensington™ Lock

Easy to use remote with buttons to change the input sources



Exceptional Connectivity/Multiple Terminals



EP1691i Projection Distance 1.2 - 12m (16:10 Aspect Ratio)

Projection Distance (m)	Max. Horizontal Image size (m)	Min. Horizontal Image size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max. Diagonal Image Size (m)	Max. Diagonal Image Size (Inch)	Max. Image Offset (m)
1.20	0.63	0.55	0.47	0.41	0.79	31.11	0.13
2.00	1.05	0.91	0.79	0.68	1.32	51.85	0.22
2.50	1.32	1.14	0.99	0.85	1.65	64.81	0.28
3.00	1.58	1.36	1.19	1.03	1.98	77.77	0.33
4.00	2.11	1.82	1.58	1.37	2.63	103.70	0.44
5.00	2.63	2.27	1.98	1.71	3.29	129.62	0.55
6.00	3.16	2.73	2.37	2.05	3.95	155.55	0.66
7.00	3.68	3.18	2.77	2.39	4.61	181.47	0.78
8.00	4.21	3.64	3.17	2.73	5.27	207.40	0.89
9.00	4.74	4.09	3.56	3.08	5.93	233.32	1.00
10.00	5.26	4.55	3.96	3.42	6.58	259.25	1.11
11.00	5.79	5.00	4.35	3.76	7.24	285.17	1.22
12.00	6.32	5.45	4.75	4.10	7.90	311.10	1.33

For guide purposes only

EP1691i is capable of 4:3 and 16:9 aspect ratio projection. When projecting a 4:3/16:9 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.co.uk

Panoview
Optoma recommended Screens
www.panoview.eu



*Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Please note that worn lamps will give slight variance. Exclusions: (1) Guarantee is voided if the projector is subject to damage through mis-use. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is particularly excessive (3) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other fault. **Typical lamp life achieved through testing. Will vary according to operational use and environment conditions. *** Optoma guarantees that in normal use, the DLP® imager guarantee will retain quality for at least 5 years providing consistent pixel performance. Exclusions: (1) Guarantee is voided if the projector is subject to damage through mis-use. (2) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is particularly excessive. Copyright © 2008, Optoma Europe Ltd. All other product names and company names used herein are for identifications purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments.